

USA: 1007 East Spring Street · Titusville, PA 16354 · Toll Free: 1-800-852-6537 · Telephone: (814) 827-4900 · Fax: (814) 827-2363 Canada: 50 Salome Drive · Toronto, Ontario M1S 2A8 · Toll Free: 1-800-561-3509 · Telephone: (416) 293-4151 · Fax: (416) 293-5858 Website: www.igiwax.com

EVACOTE® 7089A

EVACOTE® 7089A is a specialty formulation of petroleum waxes and polymers suitable in consistency to be utilized as a sealant and coating for fertilizer applications.

PHYSICAL PROPERTIES

	ASTM	SPECIFICATIONS		
TEST METHODS	METHOD	Minimum	Maximum	TYPICAL
Congealing Point °F (°C)	D 938	143 (61.7)	153 (67.2)	148 (64.4)
Thermosel Viscosity, cP @ 200°F (93.3°C)	D 3236	15	30	20
ASTM Color	D 6045			2.0
Odor	D 1833			2
Needle Penetration, dmm @ 77°F (25°C)	D 1321		16	10
Needle Penetration, dmm @ 100°F (37.8°C)	D 1321		35	28

Note: Physical properties for which ONLY a typical value is listed are included as additional information but may not be printed on the COA.

FDA STATUS:

This product is not intended for food contact.