USA: 1007 East Spring Street · Titusville, PA 16354 · Toll Free: 1-800-852-6537 · Telephone: (814) 827-4900 · Fax: (814) 827-2363 Canada: 50 Salome Drive · Toronto, Ontario M1S 2A8 · Toll Free: 1-800-561-3509 · Telephone: (416) 293-4151 · Fax: (416) 293-5858 Website: www.igiwax.com

IGI® 8719A

IGI® 8719A is a highly refined synthetic wax ideally suited for many applications including ink, hotmelt and thermal transfer products.

PHYSICAL PROPERTIES

	ASTM	SPECIFICATIONS		
TEST METHODS	METHOD	Minimum	Maximum	TYPICAL
Congealing Point °F (°C)	D 938	154.4 (68)	159.8 (71)	156.2 (69)
Peak Melt Point (DSC) °F (°C)		156.2 (69)	161.6 (72)	158 (70)
Kinematic Viscosity, cSt @ 212°F (100°C)	D 445	5.0	8.0	6.0
ASTM Color	D 6045	0	2.0	
Needle Penetration, dmm @ 77°F (25°C)	D 1321	10	20	15
Needle Penetration, dmm @ 110°F (43.3°C)	D 1321	25	35	29

Note: Physical properties for which ONLY a typical value is listed are included as additional information but may not be printed on the COA.

FDA STATUS:

Please contact an IGI representative for information concerning the FDA status of this product.

3/4/13

WARRANTY DISCLAIMER STATEMENT