USA: 1007 East Spring Street · Titusville, PA 16354 · Toll Free: 1-800-852-6537 · Telephone: (814) 827-4900 · Fax: (814) 827-2363 Canada: 50 Salome Drive - Toronto, Ontario M1S 2A8 - Toll Free: 1-800-561-3509 - Telephone: (416) 293-4151 - Fax: (416) 293-5858 Website: www.igiwax.com

## MICROSERE® 5715A

MICROSERE® 5715A is a high quality microcrystalline wax ideally suited for laminating applications in foodstuffs and general purpose packaging.

Laminates produced show excellent initial seal strength, good resistance to aging and are resistant to strike through at high ambient temperatures.

## PHYSICAL PROPERTIES

	ASTM	SPECIFICATIONS		
TEST METHODS	METHOD	Minimum	Maximum	TYPICAL
Drop Melt Point °F (°C)	D 127	165 (73.9)	177 (80.6)	171 (77.2)
Kinematic Viscosity, cSt @ 212°F (100°C)	D 445	13.8	19.0	17.9
Oil Content, Wt%	D 721		2.5	1.0
Saybolt Color	D 6045	+16		+16
Odor	D 1833		2	1
Needle Penetration, dmm @ 77°F (25°C)	D 1321	20	35	26

Note: Physical properties for which ONLY a typical value is listed are included as additional information but may not be printed on the COA.

## FDA STATUS:

This product meets the FDA requirements set forth in 21 CFR 178.3710 for use in contact with food. For additional FDA compliance information, please contact your IGI Sales Representative.

7/6/20