USA: 1007 East Spring Street · Titusville, PA 16354 · Toll Free: 1-800-852-6537 · Telephone: (814) 827-4900 · Fax: (814) 827-2363 Canada: 50 Salome Drive · Toronto, Ontario M1S 2A8 · Toll Free: 1-800-561-3509 · Telephone: (416) 293-4151 · Fax: (416) 293-5858 Website: www.igiwax.com

## MICROSERE® 5799A

MICROSERE® 5799A is a laminating-grade, mid-melt, microcrystalline wax that is used in a variety of applications.

## PHYSICAL PROPERTIES

|  | ASTM   | SPECIFICATIONS |            |            |
|--|--------|----------------|------------|------------|
| TEST METHODS                             | METHOD | Minimum        | Maximum    | TYPICAL    |
| Drop Melt Point °F (°C)                  | D 127  | 165 (73.9)     | 177 (80.6) | 171 (77.2) |
| Kinematic Viscosity, cSt @ 212°F (100°C) | D 445  | 13.80          | 19.0       | 17.9       |
| Oil Content, Wt%                         | D 721  |                | 2.5        | 1.0        |
| ASTM Color                               | D 6045 |                | 1.5        | 1.3        |
| Odor                                     | D 1833 |                | 2          | 1          |
| Needle Penetration, dmm @ 77°F (25°C)    | D 1321 | 20             | 30         | 26         |

Note: Physical properties for which ONLY a typical value is listed are included as additional information but may not be printed on the COA.

## FDA STATUS:

This product meets the FDA requirements set forth in 21 CFR 178.3710 for use in contact with food. For additional FDA compliance information, please contact your IGI Sales Representative.

7/26/19