

USA: 1007 East Spring Street · Titusville, PA 16354 · Toll Free: 1-800-852-6537 · Telephone: (814) 827-4900 · Fax: (814) 827-2363 Canada: 50 Salome Drive · Toronto, Ontario M1S 2A8 · Toll Free: 1-800-561-3509 · Telephone: (416) 293-4151 · Fax: (416) 293-5858 Website: www.igiwax.com

MICROSERE® 5909A

MICROSERE® 5909A is a high-melt, microcrystalline wax that is used in a variety of applications including; plastics, adhesives, candles, cosmetics, food coatings, inks, lubricants, personal care, polish, and textiles.

PHYSICAL PROPERTIES

	ASTM	SPECIFICATIONS		
TEST METHODS	METHOD	Minimum	Maximum	TYPICAL
Drop Melt Point °F (°C)	D 127	192 (88.9)	200 (93.3)	194 (90)
Kinematic Viscosity, cSt @ 212°F (100°C)	D 445	16.5		20.1
Oil Content, Wt%	D 721		1.8	0.5
Flash Point (P.M.), °F (°C)	D 93	500 (260)		515 (268)
ASTM Color	D 6045		0.5	0.2
Odor	D 1833		2	1
Needle Penetration, dmm @ 77°F (25°C)	D 1321		10	7

Note: Physical properties for which ONLY a typical value is listed are included as additional information but may not be printed on the COA.

FDA STATUS:

This product meets the FDA requirements set forth in 21 CFR 178.3710 for use in contact with food. For additional FDA compliance information, please contact your IGI Sales Representative.

4/11/17

WARRANTY DISCLAIMER STATEMENT