USA: 1007 East Spring Street · Titusville, PA 16354 · Toll Free: 1-800-852-6537 · Telephone: (814) 827-4900 · Fax: (814) 827-2363 Canada: 50 Salome Drive · Toronto, Ontario M1S 2A8 · Toll Free: 1-800-561-3509 · Telephone: (416) 293-4151 · Fax: (416) 293-5858 Website: www.igiwax.com

PARAFFLEX® 4630A

PARAFFLEX® 4630A is a soft, smooth and creamy looking blend specially formulated for single pour container candles.

PHYSICAL PROPERTIES

	ASTM	SPECIFICATIONS		
TEST METHODS	METHOD	Minimum	Maximum	TYPICAL
Congealing Point °F (°C)	D 938	117 (47.2)	128 (53.3)	120 (48.9)
Kinematic Viscosity, cSt @ 212°F (100°C)	D 445	5.0	7.5	7.0
Saybolt Color	D 6045	+8		+13
Odor	D 1833		1	0.5
Needle Penetration, dmm @ 77°F (25°C)	D 1321	95	135	125

Note: Physical properties for which ONLY a typical value is listed are included as additional information but may not be printed on the COA.

FDA STATUS:

Please contact an IGI representative for information concerning the FDA status of this product.