

USA: 1007 East Spring Street · Titusville, PA 16354 · Toll Free: 1-800-852-6537 · Telephone: (814) 827-4900 · Fax: (814) 827-2363 Canada: 50 Salome Drive · Toronto, Ontario M1S 2A8 · Toll Free: 1-800-561-3509 · Telephone: (416) 293-4151 · Fax: (416) 293-5858 Website: www.igiwax.com

PARAFFLEX® 4797A

PARAFFLEX® 4797A is a premium grade cascading wax for treatment of corrugated paperboard.

PHYSICAL PROPERTIES

	ASTM	SPECIFICATIONS		
TEST METHODS	METHOD	Minimum	Maximum	TYPICAL
Congealing Point °F (°C)	D 938	130 (54.4)	145 (62.8)	135 (57.2)
Kinematic Viscosity, cSt @ 212°F (100°C)	D 445	4.6	6.6	5.6
Odor	D 1833		1.5	1
ASTM Color	D 6045		0.5	0
Needle Penetration, dmm @ 77°F (25°C)	D 1321			13

Note: Physical properties for which ONLY a typical value is listed are included as additional information but may not be printed on the COA.

APPLICATION CONDITIONS:

Temperature: 200-220°F (93-104°C) for dry waxing / 170-190°F (77-88°C) for wet waxing

FDA STATUS:

This product meets the FDA requirements set forth in 21 CFR 176.170 and 176.180 for use in contact with food, subject to the finished food-contact article meeting the extractive limitations under the intended conditions of use.

5/6/15