# SAFETY DATA SHEET



Version # 02

Issue date: 16-August-2015 Revision date: 19-October-2022 Supersedes date: 16-August-2015

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

4700 - 4800 Series Products (Nochek®, Parafflex®, Astorlite®)

of the mixture

Registration number

See page 11

**Synonyms** SDS number

4700 - 4800 Series (928749)\_Europe\_English

1.2. Relevant identified uses of the substance or mixture and uses advised against

Various end uses e.g. additional processing, candles, tire and rubber additives, adhesives, food Identified uses

contact coatings etc.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

The International Group Inc. Manufacturer

**Address** 50 Salome Dr

Toronto, Ontario, M1S 2A8

Canada

+1-(416)-293-4151 **Telephone** INTERTEK FRANCE Only Representative **Address** Allée de la Fosse Moret

Eco parc 2

27400 Heudebouville

France

+33 2 79 23 03 49 **Telephone** E-mail if.reach@intertek.com 1.4. Emergency telephone +1-(416)-293-4151

number

+1-(800)-561-3509

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

## 2.2. Label elements

# Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms None. None. Signal word

The mixture does not meet the criteria for classification. **Hazard statements** 

**Precautionary statements** 

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Store away from incompatible materials. Storage

Dispose of waste and residues in accordance with local authority requirements. **Disposal** 

Supplemental information on

None.

the label

4700 - 4800 Series SDS EU

928749 Version #: 02 Revision date: 19-October-2022 Issue date: 16-August-2015 1/11

### 2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or

greater than 0.1% by weight.

The mixture does not contain any substances having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0.1% by weight.

# SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

The components are not hazardous or are below required disclosure limits.

## **SECTION 4: First aid measures**

**General information** 

If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance.

#### 4.1. Description of first aid measures

Inhalation

Solid: No specific first aid measures noted. If fumes from heated product are inhaled: Move to fresh air. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact

Solid: No specific first aid measures noted. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water, and see a physician for removal of adhering material and treatment of burn.

Eye contact

Solid: No specific first aid measures noted. Exposure to fumes, vapors or smoke of over heated product can result in irritation of eyes. Direct contact of molten material will cause injury and burns. When handling of molten product eye shield must be worn at all times. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Should an accident occur, flush eyes with generous amounts of water for at least 15 minutes. Administer prompt first aid measures. Get medical attention if irritation develops and persists.

Ingestion

Solid: No specific first aid measures noted. Not acutely toxic by ingestion. If material is ingested, do not induce vomiting. Contact with hot product may cause severe burns. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Eye and skin contact: When heated, contact with molten product can cause injury and burns.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

#### SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted. Will burn if involved in a fire.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

By heating and fire, irritating vapours/gases may be formed. During fire, hazardous combustion products are released that may include: Carbon oxides. Aldehydes. Ketones.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Use water spray to cool unopened containers. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if

possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with

water until well after the fire is out.

# **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Wear appropriate personal protective equipment.

For emergency responders

Keep unnecessary personnel away. Do not breathe mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Wear appropriate protective equipment and clothing during clean-up.

 4700 - 4800 Series
 SDS EU

 928749
 Version #: 02
 Revision date: 19-October-2022
 Issue date: 16-August-2015
 2 / 11

## 6.2. Environmental precautions

## 6.3. Methods and material for containment and cleaning up

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Handle as a thermoplastic. With molten spills, allow the material to solidify and cool. Keep material out of sewers and watercourses by diking or impounding. Recover and place into appropriate containers for recycling or disposal, according to prevailing local, regional and national laws.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Allow material to solidify, and scrape up. Following product recovery, flush area with

Small Spills: Where possible allow molten material to solidify naturally. Scrape up the spilled material. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

## 6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers. Do not handle until all safety precautions have been read and understood. Heat only in areas with appropriate exhaust ventilation. Do not breathe fume/mist/vapors. Avoid contact with molten material. When using, do not eat, drink or smoke. Observe good industrial hygiene practices. Do not empty into drains. Avoid release to the environment. Wash contaminated clothing before reuse. The material is a solid at room temperature exhibiting elevated temperature softening characteristics. Above its softening point, the material liquefies and flows more readily as the temperature increases. The material may be used as a hot liquid for application purposes and requires caution in handling.

# 7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers.

# 7.3. Specific end use(s)

Various end uses e.g. additional processing, candles, tire and rubber additives, adhesives, food contact coatings etc. Observe industrial sector guidance on best practices.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

Occupational exposure limits

Belgium.	Exposure	Limit \	/alues
----------	----------	---------	--------

Components	Туре	Value	Form
Hydrocarbons	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Paraffinic hydrocarbons	TWA	2 mg/m3	Fume.

#### Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work Components Value **Type** Hydrocarbons TWA 5 mg/m3

# Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended

Components	Туре	Value	Form	
Paraffinic hydrocarbons	MAC	2 mg/m3	Fume.	
	STEL	6 mg/m3	Fume.	
Czech Republic. OELs. Governn	nent Decree 361			
Components	Туре	Value	Form	
Hydrocarbons	Ceiling	10 mg/m3	Aerosol	
	TWA	5 mg/m3	Aerosol	
Denmark. Exposure Limit Values	S			
Components	Туре	Value	Form	
Hydrocarbons	TLV	1 mg/m3	Mist.	
Paraffinic hydrocarbons	TLV	2 mg/m3	Fume.	

4700 - 4800 Series SDS EU Issue date: 16-August-2015

928749 Version #: 02 Revision date: 19-October-2022

Estonia. OELs. Occupational Exposure L Components	imits of Hazardous Substances (R Type	egulation No. 105/20 Value	01, Annex), as amended Form
Paraffinic hydrocarbons	TWA	2 mg/m3	Vapour.
Finland. Workplace Exposure Limits Components	Туре	Value	Form
Hydrocarbons	TWA	5 mg/m3	Mist.
Paraffinic hydrocarbons	TWA	1 mg/m3	Fume.
France. Threshold Limit Values (VLEP) for Components	or Occupational Exposure to Chem Type	nicals in France, INR Value	S ED 984 Form
Paraffinic hydrocarbons	VME	2 mg/m3	Fume.
Regulatory status: Indicative limit (\	/L)	· ·	
Germany. DFG MAK List (advisory OELs in the Work Area (DFG)	). Commission for the Investigatio	n of Health Hazards	of Chemical Compounds
Components	Туре	Value	Form
Hydrocarbons	TWA	5 mg/m3	Respirable fraction.
Greece. OELs (Decree No. 90/1999, as an Components	nended) Type	Value	Form
Hydrocarbons	TWA	5 mg/m3	Mist.
Paraffinic hydrocarbons	STEL	6 mg/m3	Fume.
· · · · · · · · · · · · · · · · · · ·	TWA	2 mg/m3	Fume.
Hungary. OELs. Joint Decree on Chemica Components	al Safety of Workplaces Type	Value	
Hydrocarbons	TWA	5 mg/m3	
Iceland. OELs. Regulation 390/2009 on Po	ollution Limits and Measures to Ro Type	-	e Workplace, as amended Form
Hydrocarbons	TWA	1 mg/m3	Mist.
Paraffinic hydrocarbons	TWA	2 mg/m3	Fume.
Ireland. Occupational Exposure Limits Components	Туре	Value	Form
Paraffinic hydrocarbons	STEL	6 mg/m3	Fume.
·	TWA	2 mg/m3	Fume.
Italy. OELs Components	Туре	Value	Form
Hydrocarbons	TWA	5 mg/m3	Inhalable fraction.
Paraffinic hydrocarbons	TWA	2 mg/m3	Fume.
Latvia. OELs. Occupational exposure lim Components	it values of chemical substances i Type	n work environment Value	
Hydrocarbons	TWA	5 mg/m3	
Lithuania. OELs. Limit Values for Chemic Components		-	HN 23:2007) Form
Hydrocarbons	STEL	3 mg/m3	Fume and mist.
•	TWA	1 mg/m3	Fume and mist.
Netherlands. OELs (binding) Components	Туре	Value	Form
Hydrocarbons	TWA	5 mg/m3	Mist.
Norway. Administrative Norms for Conta		Value	Form
Hydrocarbons	TLV	1 mg/m3	Mist.
Paraffinic hydrocarbons	TLV	2 mg/m3	Fume.
4700 4800 Sories	v	2 mg/mo	, dillo.

 4700 - 4800 Series
 SDS EU

 928749
 Version #: 02
 Revision date: 19-October-2022
 Issue date: 16-August-2015
 4 / 11

Poland. Maximum permiss 1286/2018, Annex 1)	sible concentrations and intensities of har	mful factors in the work	environment (Dz.U.Poz.
Components	Type	Value	Form

ommended monitoring Follow standard monitoring procedures.  ived no effect levels Not available.  ELs)  dicted no effect Not available.	Components	Туре	Value	Form
Components   Type   Value   Form	Paraffinic hydrocarbons	TWA	2 mg/m3	Inhalable fraction.
Paraffinic hydrocarbons TWA 2 mg/m3 Fume.  Romania, OELs. Protection of workers from exposure to chemical agents at the workplace Components  Type  National STEL 10 mg/m3  TWA 5 mg/m3  Fume.  Paraffinic hydrocarbons  STEL 6 mg/m3 Fume.  SIONAKIA. OELs. Decree of the government of the SIovak Republic concerning protection of health in work with chemical agents  Components  Type  Value  Form  Hydrocarbons  TWA 1 mg/m3 Fume and mist. 5 ppm Fume and mist. 7 ppe  Value  Form  Paraffinic hydrocarbons  TWA 2 mg/m3 Fume.  SIovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Components  Type  Value  Form  Paraffinic hydrocarbons  STEL 3 mg/m3 Fume and mist. 15 ppm Fume and mist. 16 mg/m3 Fume.  Spain. Occupational Exposure Limits Components  Type  Value  Form  Hydrocarbons  STEL 0 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Paraffinic hydrocarbons  STEL 10 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Paraffinic hydrocarbons  STEL 10 mg/m3 Mist.  TWA 2 mg/m3 Fume.  Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended Components  Type  Value  Form  Hydrocarbons  Type  Value  Form  Hydroca				Form
Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Components Type Value Form  TWA 5 mg/m3 Fume.  TWA 2 mg/m3 Fume.  STEL 6 mg/m3 Fume.  TWA 2 mg/m3 Fume.  SIovakia. OELs. Decree of the government of the Slovak Republic concerning protection of health in work with chemic agents Components Type Value Form Fume and mist. 5 ppm Fume and mist. 6 mg/m3 Fume.  Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemic algents Components Type Value Form  Hydrocarbons STEL 3 mg/m3 Fume and mist. 15 ppm Fume and mist. 16 ppm/m3 Mist. 17 ppm Mist. 18 ppm/m3 Mist. 18	Hydrocarbons	TWA	5 mg/m3	Inhalable fraction.
Components         Type         Value         Form           Hydrocarbons         STEL         10 mg/m3         TWA           Paraffinic hydrocarbons         STEL         6 mg/m3         Fume.           Slovakia. OELs. Decree of the government of the Slovak Republic concerning protection of health in work with chemical agents         Type         Value         Form           Hydrocarbons         TWA         1 mg/m3         Fume and mist.           Paraffinic hydrocarbons         TWA         1 mg/m3         Fume and mist.           Paraffinic hydrocarbons         TWA         2 mg/m3         Fume and mist.           Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents         Type         Value         Form           Paraffinic hydrocarbons         STEL         3 mg/m3         Fume and mist.           Paraffinic hydrocarbons         STEL         6 mg/m3         Fume and mist.           Paraffinic hydrocarbons         STEL         15 ppm         Fume and mist.           Spain. Occupational Exposure Limits         Type         Value         Form           Hydrocarbons         STEL         10 mg/m3         Mist.           Paraffinic hydrocarbons         TWA         2 mg/m3         Fume.           Sweden. OELs (Annex 1)	Paraffinic hydrocarbons	TWA	2 mg/m3	Fume.
Paraffinic hydrocarbons STEL 6 mg/m3 Fume.  Slovakia. OELs. Decree of the government of the Slovak Republic concerning protection of health in work with chemic agents Components Type Value Form  Hydrocarbons TWA 1 mg/m3 Fume and mist. 5 ppm Fume and mist. 6 ppm Fume and mist. 7 ppe Value Form  Hydrocarbons STEL 3 mg/m3 Fume.  Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Components Type Value Form  Hydrocarbons STEL 3 mg/m3 Fume and mist. 15 ppm Fume and mist. 16 ppm Fume and mist. 16 ppm Fume and mist. 18 ppm Fume and mist. 19 ppm Fume		·	•	Form
Paraffinic hydrocarbons   STEL   6 mg/m3   Fume.   TWA   2 mg/m3   Fume.   TWA   2 mg/m3   Fume.   TWA   2 mg/m3   Fume.   TWA   1 mg/m3   Fume and mist.   Form   Fume and mist.   Fume and mist.   Fume and mist.   Form   Fume and mist.   Fume and mist	Hydrocarbons	STEL	10 mg/m3	
Slovakia. OELs. Decree of the government of the Slovak Republic concerning protection of health in work with chemical agents Components  Type  Value  Form  Hydrocarbons  TWA  1 mg/m3 Fume and mist. 5 ppm Fume and mist. 5 ppm Fume and mist. 5 ppm Fume and mist. 7 mg/m3 Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Components  Type Value Form  Hydrocarbons  STEL  3 mg/m3 Fume and mist. 15 ppm Fume and mist. 16 mg/m3 Fume.  Spain. Occupational Exposure Limits Components  Type Value Form  Hydrocarbons  STEL  10 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Faraffinic hydrocarbons  STEL  10 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Fume.  Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended Components  Type Value Form  Hydrocarbons  STEL  3 mg/m3 Mist.  TWA 1 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components  Type Value Form  Hydrocarbons  TWA 5 mg/m3 Mist.  Work 1 mg/m3 Mist.  Work 1 mg/m3 Mist.  Work 1 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components  Type Value Form  Hydrocarbons  TWA 5 mg/m3 Inhalable fraction.  Paraffinic hydrocarbons  TWA 5 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components  Type Value Form  Hydrocarbons  TWA 5 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components  Type Value Form  Hydrocarbons  Follow standard monitoring procedures.  Evel no effect levels ELs)  Not available.		TWA	5 mg/m3	
Slovakia. OELs. Decree of the government of the Slovak Republic concerning protection of health in work with chemical agents Components Type Value Form  Hydrocarbons TWA 1 mg/m3 Fume and mist. 5 ppm Fume and mist. 5 ppm Fume and mist. 5 ppm Form Form  Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Components Type Value Form  Hydrocarbons STEL 3 mg/m3 Fume and mist. 15 ppm Fume and mist. 16 mg/m3 Fume.  Spain. Occupational Exposure Limits Components Type Value Form  Hydrocarbons STEL 10 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Paraffinic hydrocarbons TWA 5 mg/m3 Mist.  Paraffinic hydrocarbons TWA 5 mg/m3 Mist.  Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended Components Type Value Form  Hydrocarbons STEL 3 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form  Hydrocarbons TWA 5 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form  Hydrocarbons TWA 5 mg/m3 Inhalable fraction. Paraffinic hydrocarbons TWA 5 mg/m3 Respirable fume.  UKL. EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons STEL 6 mg/m3 Fume.  Omponents Form  Paraffinic hydrocarbons FUWA 2 mg/m3 Fume.  Ogical limit values No biological exposure limits noted for the ingredient(s).  ommended monitoring Follow standard monitoring procedures.  red on effect levels Not available.	Paraffinic hydrocarbons	STEL	6 mg/m3	Fume.
agents Components Type Value Form Hydrocarbons TWA 1 mg/m3 Fume and mist. 5 ppm Fume and mist. 6 ppm Fume and mist. 7 ppm Form Form Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Components Type Value Form Hydrocarbons STEL 3 mg/m3 Fume and mist. 15 ppm Fume and mist. 16 mg/m3 Fume.  Spain. Occupational Exposure Limits 17 mg/m3 Mist. 18 mg/m3		TWA	2 mg/m3	Fume.
Type Value Form Hydrocarbons TWA 1 mg/m3 Fume and mist. 5 ppm Fume and mist. 7 ppm Fume and mist. 8 ppm Fume. 8 ppm Value Form 9 ppm Fume and mist. 15 ppm Fume and mist. 16 mg/m3 Fume. 8 ppain. Occupational Exposure Limits 8 ppm Fume. 8 ppain. Occupational Exposure Limits 8 ppm Fume. 9 ppm Fume. 9 ppm Fume and mist. 10 mg/m3 Fume. 9 ppm Fume. 10 mg/m3 Mist. 10 m		the government of the Slovak Repub	lic concerning protection of	health in work with chemic
Paraffinic hydrocarbons TWA 2 mg/m3 Fume.  Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Components Type Value Form  Hydrocarbons STEL 3 mg/m3 Fume and mist.  15 ppm Pume and mist.  15 ppm Fume and mist.  16 mg/m3 Fume and mist.  17 ppm Value Form  17 ppm Pump and mist.  18 ppm And mist.  18 ppm And mist.  18 ppm And mist.  18 ppm An	•	Туре	Value	Form
Paraffinic hydrocarbons			1 mg/m3	Fume and mist.
Paraffinic hydrocarbons  TWA  2 mg/m3 Fume.  Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Type  Walue Form  Hydrocarbons  STEL  3 mg/m3 Fume and mist. 15 ppm Fume and mist. 6 mg/m3 Fume.  Spain. Occupational Exposure Limits Components  Type Value Form  Hydrocarbons  STEL  10 mg/m3 Mist. TWA 5 mg/m3 Mist.  Paraffinic hydrocarbons  STEL  10 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Paraffinic hydrocarbons  STEL  10 mg/m3 Mist.  Fume.  Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values  Gomponents  Type Value Form  Hydrocarbons  TWA 1 mg/m3 Mist.  TWA 1 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components  Type Value Form  Hydrocarbons  TWA 5 mg/m3 Mist.  TWA 5 mg/m3 Mist.  TWA 1 mg/m3 Mist.  SWitzerland. SUVA Grenzwerte am Arbeitsplatz Components  Type Value Form  Hydrocarbons  TWA 5 mg/m3 Inhalable fraction.  Paraffinic hydrocarbons  TWA 5 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components  Type Value Form  Paraffinic hydrocarbons  TWA 2 mg/m3 Fume.  OK. EH40 Workplace Exposure Limits (WELs) Components  Type Value Form  Form  Paraffinic hydrocarbons  TWA 2 mg/m3 Fume.  Form  Paraffinic hydrocarbons  TWA 2 mg/m3 Fume.  Form  Paraffinic hydrocarbons  Follow standard monitoring procedures.  Form  Follow standard monitoring procedures.  Form  Follow standard monitoring procedures.	-		·	Fume and mist.
Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Components Type Value Form  Hydrocarbons STEL 3 mg/m3 Fume and mist. 15 ppm Fume and mist. 15 ppm Fume and mist. Paraffinic hydrocarbons STEL 6 mg/m3 Fume.  Spain. Occupational Exposure Limits Components Type Value Form  Hydrocarbons STEL 10 mg/m3 Mist. TWA 5 mg/m3 Mist. Paraffinic hydrocarbons TWA 2 mg/m3 Fume.  Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended Components Type Value Form  Hydrocarbons STEL 3 mg/m3 Mist. TWA 1 mg/m3 Mist.  TWA 1 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form  Hydrocarbons TWA 5 mg/m3 Inhalable fraction. Paraffinic hydrocarbons TWA 5 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Hydrocarbons Type Value Form  Hydrocarbons TWA 5 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons Type Value Form  Follow standard monitoring procedures.  Form  Follow standard monitoring procedures.  Follow standard monitoring procedures.  Follow standard monitoring procedures.	Paraffinic hydrocarbons	TWA	• •	Fume.
Paraffinic hydrocarbons  STEL  15 ppm Fume and mist. 6 mg/m3 Fume.  Spain. Occupational Exposure Limits Components  Type Value Form  Hydrocarbons STEL 10 mg/m3 Mist. TWA 5 mg/m3 Fume.  Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values Assembly Components Type Value Form  Hydrocarbons STEL 3 mg/m3 Mist. TWA 1 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form  Hydrocarbons TWA 5 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form  Hydrocarbons TWA 5 mg/m3 Inhalable fraction. Paraffinic hydrocarbons TWA 2 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons Type Value Form  Paraffinic hydrocarbons Type Value Form  Paraffinic hydrocarbons Form  Paraffinic hydrocarbons Form  Paraffinic hydrocarbons No biological exposure limits noted for the ingredient(s).  TWA 2 mg/m3 Fume. Form  Paraffinic hydrocarbons Follow standard monitoring procedures.  STEL 6 mg/m3 Fume. Form  Paraffinic hydrocarbons Follow standard monitoring procedures.  STEL 5 mg/m3 Fume. Form  Paraffinic hydrocarbons Follow standard monitoring procedures.  STEL 6 mg/m3 Fume. Form	Slovakia. OELs. Regulation		of health in work with chem	
Paraffinic hydrocarbons  STEL Spain. Occupational Exposure Limits Components  Type Value Form  Hydrocarbons STEL 10 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Paraffinic hydrocarbons TWA 2 mg/m3 Fume.  Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values Gomponents Type Value Form  Hydrocarbons STEL 3 mg/m3 Mist.  TWA 1 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form  Hydrocarbons TWA 5 mg/m3 Inhalable fraction.  Paraffinic hydrocarbons TWA 5 mg/m3 Inhalable fraction.  Paraffinic hydrocarbons TWA 2 mg/m3 Respirable fume.  UK, EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons TWA 2 mg/m3 Fume.  Occupational Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons Type Value Form  Paraffinic hydrocarbons TWA 2 mg/m3 Fume.  Occupational Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons Follow standard monitoring procedures.  Occupational Exposure Limits noted for the ingredient(s).	Hydrocarbons	STEL	3 mg/m3	Fume and mist.
Spain. Occupational Exposure Limits Components  Type  Value  Form  Hydrocarbons  STEL  TWA  5 mg/m3  Mist.  Paraffinic hydrocarbons  TWA  2 mg/m3  Fume.  Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended Components  Type  Value  Form  Hydrocarbons  STEL  3 mg/m3  Mist.  TWA  1 mg/m3  Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components  Type  Value  Form  Hydrocarbons  TWA  5 mg/m3  Inhalable fraction.  Paraffinic hydrocarbons  TWA  2 mg/m3  Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components  Type  Value  Form  Paraffinic hydrocarbons  STEL  6 mg/m3  Fume. TWA  2 mg/m3  Fume.  Ocical limit values  No biological exposure limits noted for the ingredient(s).  Total components  Not available.  ELs.)  Mot available.	•		15 ppm	Fume and mist.
Type Value Form  Hydrocarbons STEL 10 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Paraffinic hydrocarbons TWA 2 mg/m3 Fume.  Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended Components Type Value Form  Hydrocarbons STEL 3 mg/m3 Mist.  TWA 1 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form  Hydrocarbons TWA 5 mg/m3 Inhalable fraction.  Paraffinic hydrocarbons TWA 5 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons TWA 2 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons Type Value Form  Paraffinic hydrocarbons STEL 6 mg/m3 Fume.  TWA 2 mg/m3 Fume.  TWA 2 mg/m3 Fume.  Form  Paraffinic hydrocarbons Follow standard monitoring procedures.  Wed no effect levels ELs)  Not available.	Paraffinic hydrocarbons	STEL	• •	Fume.
Hydrocarbons  STEL 10 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Paraffinic hydrocarbons TWA 2 mg/m3 Fume.  Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended Components Type Value Form  Hydrocarbons STEL 3 mg/m3 Mist.  TWA 1 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form  Hydrocarbons TWA 5 mg/m3 Inhalable fraction.  Paraffinic hydrocarbons TWA 2 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons STEL 6 mg/m3 Fume. TWA 2 mg/m3 Fume.  Occupational Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons STEL 6 mg/m3 Fume. TWA 2 mg/m3 Fume.  Occupational Exposure Limits (WELs) Components Form  Paraffinic hydrocarbons STEL 6 mg/m3 Fume. TWA 2 mg/m3 Fume.  Occupational Exposure Limits (WELs) Components Form  Paraffinic hydrocarbons STEL 6 mg/m3 Fume.  Occupational Exposure Limits (WELs) Components Form  Paraffinic hydrocarbons STEL 7 mg/m3 Fume.  Occupational Exposure Limits (WELs) Components Form  Paraffinic hydrocarbons STEL 7 mg/m3 Fume.  Occupational Exposure Limits (WELs) Components Form  Paraffinic hydrocarbons STEL 9 mg/m3 Fume.  Occupational Exposure Limits (WELs) Components Form  Paraffinic hydrocarbons STEL 9 mg/m3 Fume.  Occupational Exposure Limits (WELs) Components Form  No biological exposure limits noted for the ingredient(s).  Occupational Exposure Limits (WELs) Components Form  Not available.			Value	Form
TWA 5 mg/m3 Mist.  Paraffinic hydrocarbons TWA 2 mg/m3 Fume.  Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended Components Type Value Form  Hydrocarbons STEL 3 mg/m3 Mist.  TWA 1 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form  Hydrocarbons TWA 5 mg/m3 Inhalable fraction.  Paraffinic hydrocarbons TWA 2 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons TWA 2 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons STEL 6 mg/m3 Fume.  TWA 2 mg/m3 Fume.  TWA 2 mg/m3 Fume.  TWA 2 mg/m3 Fume.  Follow standard monitoring procedures.  Societal limit values No biological exposure limits noted for the ingredient(s).  TWA 2 mg/m3 Fume.  Follow standard monitoring procedures.  Stella Not available.			10 mg/m3	Mist.
Paraffinic hydrocarbons  TWA  2 mg/m3  Fume.  Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended  Components  Type  Value  Form  Hydrocarbons  STEL  TWA  1 mg/m3  Mist.  TWA  1 mg/m3  Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components  Type  Value  Form  Hydrocarbons  TWA  5 mg/m3  Inhalable fraction.  Paraffinic hydrocarbons  TWA  2 mg/m3  Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components  Type  Value  Form  Paraffinic hydrocarbons  STEL  Gomponents  Type  Value  Form  Paraffinic hydrocarbons  STEL  Gomponents  TWA  2 mg/m3  Fume.  TWA  2 mg/m3  Fume.  Form  Paraffinic hydrocarbons  STEL  TWA  2 mg/m3  Fume.  Form  Follow standard monitoring procedures.  Somenended monitoring Follow standard monitoring procedures.  Steed no effect levels  ELs)  dicted no effect  Not available.	,		-	
Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended Components Type Value Form  Hydrocarbons STEL 3 mg/m3 Mist.  TWA 1 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form  Hydrocarbons TWA 5 mg/m3 Inhalable fraction.  Paraffinic hydrocarbons TWA 2 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons STEL 6 mg/m3 Fume.  TWA 2 mg/m3 Fume.  logical limit values No biological exposure limits noted for the ingredient(s).  ommended monitoring Follow standard monitoring procedures.  lived no effect levels ELs)  dicted no effect Not available.	Paraffinic hydrocarbons		•	
Type Value Form  Hydrocarbons STEL 3 mg/m3 Mist.  TWA 1 mg/m3 Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form  Hydrocarbons TWA 5 mg/m3 Inhalable fraction.  Paraffinic hydrocarbons TWA 2 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons STEL 6 mg/m3 Fume.  TWA 2 mg/m3 Fume.  TWA 2 mg/m3 Fume.  Hydrocarbons Follow standard monitoring procedures.  Hydrocarbons TwA 2 mg/m3 Fume.  Hydrocarbons STEL 6 mg/m3 Fume.  Hydrocarbons Follow standard monitoring procedures.  Hydrocarbons TwA 2 mg/m3 Fume.  Hydrocarbons Follow standard monitoring procedures.  Hydrocarbons TwA 5 mg/m3 Fume.  Hydrocarbons Follow standard monitoring procedures.  Hydrocarbons TwA 5 mg/m3 Fume.	Sweden. OELs (Annex 1).		· ·	
Hydrocarbons  STEL TWA  1 mg/m3  Mist.  TWA  1 mg/m3  Mist.  Switzerland. SUVA Grenzwerte am Arbeitsplatz Components  Type  Value  Form  Hydrocarbons  TWA  5 mg/m3  Inhalable fraction.  Paraffinic hydrocarbons  TWA  2 mg/m3  Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components  Type  Value  Form  Paraffinic hydrocarbons  STEL 6 mg/m3 Fume.  TWA 2 mg/m3  Fume.  TWA 2 mg/m3  Fume.  Form  Ogical limit values No biological exposure limits noted for the ingredient(s).  SOMMENDE STEL SOMMEND STEL		Туре	Value	Form
Switzerland. SUVA Grenzwerte am Arbeitsplatz Components Type Value Form  Hydrocarbons TWA 5 mg/m3 Inhalable fraction. Paraffinic hydrocarbons TWA 2 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons STEL 6 mg/m3 Fume. TWA 2 mg/m3 Fume.  TWA 2 mg/m3 Fume.  Jume.  Jume.  Jume  Topical limit values Jume  Topical limits noted for the ingredient(s).  Jume  Topical limit values Jume  Topical limits noted for the ingredient(s).  Jume  Topical limits noted for the ingredient(s).  Jume  Topical limits noted for the ingredient(s).  Jume  Topical limit values Jume  Topical limits noted for the ingredient(s).	Hydrocarbons		3 mg/m3	Mist.
Type Value Form  Hydrocarbons TWA 5 mg/m3 Inhalable fraction.  Paraffinic hydrocarbons TWA 2 mg/m3 Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs) Components Type Value Form  Paraffinic hydrocarbons STEL 6 mg/m3 Fume.  TWA 2 mg/m3 Fume.  TWA 2 mg/m3 Fume.  logical limit values No biological exposure limits noted for the ingredient(s).  commended monitoring Follow standard monitoring procedures.  lived no effect levels Not available.  ELs)  dicted no effect Not available.		TWA	1 mg/m3	Mist.
Hydrocarbons  TWA  TWA  TWA  TWA  TWA  TWA  TWA  TW		•	Value	Form
Paraffinic hydrocarbons  TWA  2 mg/m3  Respirable fume.  UK. EH40 Workplace Exposure Limits (WELs)  Components  Type  Value  Form  Paraffinic hydrocarbons  STEL  TWA  2 mg/m3  Fume.  TWA  2 mg/m3  Fume.  TWA  2 mg/m3  Fume.  Form  Paraffinic hydrocarbons  STEL  TWA  2 mg/m3  Fume.  Fume.  Paraffinit values  No biological exposure limits noted for the ingredient(s).  Commended monitoring  Follow standard monitoring procedures.		<del></del>		
UK. EH40 Workplace Exposure Limits (WELs) Components  Type  Value  Form  Paraffinic hydrocarbons  STEL  TWA  2 mg/m3  Fume.  logical limit values  No biological exposure limits noted for the ingredient(s).  commended monitoring  redures  lived no effect levels  ELs)  dicted no effect  Not available.	•		·	
Components Type Value Form  Paraffinic hydrocarbons STEL TWA 2 mg/m3 Fume.  10gical limit values No biological exposure limits noted for the ingredient(s).  Follow standard monitoring procedures.  ived no effect levels ELs) dicted no effect Not available.	•		2 mg/ms	rvespirable fulfie.
TWA 2 mg/m3 Fume.  logical limit values No biological exposure limits noted for the ingredient(s).  commended monitoring cedures.  lived no effect levels ELs)  dicted no effect Not available.			Value	Form
logical limit values No biological exposure limits noted for the ingredient(s). Follow standard monitoring procedures.  ived no effect levels ELs)  dicted no effect  Not available.  Not available.	Paraffinic hydrocarbons	STEL	6 mg/m3	Fume.
ommended monitoring Follow standard monitoring procedures.  ived no effect levels Not available.  ELs)  dicted no effect Not available.		TWA	2 mg/m3	Fume.
ived no effect levels Not available.  ELs)  dicted no effect Not available.	logical limit values	No biological exposure limits noted f	or the ingredient(s).	
ELs) dicted no effect Not available.	commended monitoring cedures	Follow standard monitoring procedure	res.	
	ived no effect levels ELs)	Not available.		
	dicted no effect centrations (PNECs)	Not available.		

 4700 - 4800 Series
 SDS EU

 928749
 Version #: 02
 Revision date: 19-October-2022
 Issue date: 16-August-2015
 5 / 11

8.2. Exposure controls

Appropriate engineering

controls

Ensure adequate ventilation, especially in confined areas. Provide easy access to water supply

and eye wash facilities.

Individual protection measures, such as personal protective equipment

General information Personal protection equipment should be chosen according to the CEN standards and in

discussion with the supplier of the personal protective equipment.

**Eye/face protection** Wear approved safety goggles. Wear a face shield when working with molten material. Eye

protection should meet standard EN 166.

Skin protection

- Hand protection Wear suitable gloves tested to EN374. Suitable gloves can be recommended by the glove

supplier.

- Other The material may be utilized in molten form. Proper protective splash resistant clothing, thermal

gloves, splash resistant shoes, and eye shields must be worn to prevent injury. Use molten material in well ventilated areas. When working in confined areas, use of appropriate respiratory

gear is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Respiratory protection should meet standard EN 14387.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such

as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

work clothing and protective equipment to remove contaminants.

**Environmental exposure** 

controls

Contain spills and prevent releases and observe national regulations on emissions.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state Solid.

Form Slabs, prills, pastilles or granules.

Colour White to dark amber.

Odour None.

Odour threshold Not applicable.

Melting point/freezing point  $\Rightarrow$  46 - <= 125 °C (>= 114,8 - <= 257 °F)

Boiling point or initial boiling

point and boiling range

> 300 °C (> 572 °F)

**Flammability** Will support a flame above flash point.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 0,9 % Explosive limit - upper 7 %

(%)

Flash point > 190 °C (> 374 °F) ASTM D-93

Auto-ignition temperature Property has not been measured.

Property has not been measured.

**pH** Not applicable (material is insoluble in water).

**Kinematic viscosity** Not applicable (the material is a solid).

Solubility

Solubility (water) < 0,1 % (20 °C (68 °F))

Partition coefficient Not applicable for mixtures.

(n-octanol/water) (log value)

**Vapour pressure** < 0.01 mm Hg (25 °C (77 °F))

Density and/or relative density

**Relative density**  $>= 0.9 - <= 0.95 \text{ (Water=1) } (25 ^{\circ}\text{C } (77 ^{\circ}\text{F}))$ 

Vapour density > 5 (Air = 1)

Particle characteristics

Particle size 0,8 mm (granular form) median

9.2. Other information

4700 - 4800 Series SDS EU
928749 Version #: 02 Revision date: 19-October-2022 Issue date: 16-August-2015 6 / 11

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

**Evaporation rate** < 0,01 (Butyl acetate = 1)

Partition coefficient

(oil/water)

< 0,01

Percent volatile < 1 % v/v

**SECTION 10: Stability and reactivity** 

**10.1. Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use. Hazardous polymerisation does not

occur.

10.4. Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous

decomposition products

Decomposition of this product can generate carbon dioxide, carbon monoxide and other products

such as aldehydes and ketones depending on conditions of oxidation.

**SECTION 11: Toxicological information** 

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

**Inhalation** Not relevant at normal room temperatures. When heated, irritating vapours may be formed. Wax

fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons.

Skin contact Health injuries are not known or expected under normal use. Molten material will produce thermal

burns.

Eye contact Health injuries are not known or expected under normal use. Molten material will produce thermal

burns.

**Ingestion** Health injuries are not known or expected under normal use. Contact with hot material can cause

thermal burns which may result in permanent damage.

Symptoms Eye and skin contact: Contact with molten material may cause thermal burns.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not expected to be acutely toxic.

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Thermal burn hazard - contact with hot material may cause thermal burns.

Serious eye damage/eye

irritation

Based on available data, the classification criteria are not met.

Direct contact of molten product to the eyes will cause thermal burns and eye injury.

Respiratory sensitisationBased on available data, the classification criteria are not met.Skin sensitisationBased on available data, the classification criteria are not met.Germ cell mutagenicityBased on available data, the classification criteria are not met.CarcinogenicityBased on available data, the classification criteria are not met.Reproductive toxicityBased on available data, the classification criteria are not met.

Specific target organ toxicity -

single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

**Aspiration hazard** Not likely, due to the form of the product.

Mixture versus substance

information

No information available.

11.2. Information on other hazards

**Endocrine disrupting** 

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

Other information Exposure to vapors, fumes, or smoke from molten material handled in confined areas can

produce irritation of the respiratory tract, and possible physical discomfort to sensitive individuals.

**SECTION 12: Ecological information** 

**12.1. Toxicity**Based on available data, the classification criteria are not met for hazardous to the aquatic

environment.

4700 - 4800 Series SDS EU
928749 Version #: 02 Revision date: 19-October-2022 Issue date: 16-August-2015 7 / 11

12.2. Persistence and

degradability

No data is available on the degradability of this product.

12.3. Bioaccumulative potential

No data available on bioaccumulation.

Partition coefficient

n-octanol/water (log Kow)

Not applicable for mixtures.

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil

The product is insoluble in water. Expected to have low mobility in soil.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

12.7. Other adverse effects

No data available for this product.

# SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Residual waste

Dispose in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

EU waste code

The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company. 16 03 06

Disposal methods/information

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Special precautions

# SECTION 14: Transport information

#### **ADR**

14.1. UN number

Not regulated as dangerous goods.

14.2. UN proper shipping

Not regulated as dangerous goods.

14.3. Transport hazard class(es)

Not assigned.

Subsidiary risk

Hazard No. (ADR) Not assigned. Not assigned.

**Tunnel restriction code** 14.4. Packing group Not assigned.

14.5. Environmental hazards No.

14.6. Special precautions

Not assigned.

for user

RID

14.1. UN number

Not regulated as dangerous goods.

14.2. UN proper shipping

Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk

Not assigned. 14.4. Packing group

14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

ADN

Not regulated as dangerous goods. 14.1. UN number

14.2. UN proper shipping

Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned. Subsidiary risk

14.4. Packing group Not assigned.

14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

4700 - 4800 Series SDS EU 8 / 11

928749 Version #: 02 Revision date: 19-October-2022 Issue date: 16-August-2015 IATA

14.1. UN number Not regulated as dangerous goods. Not regulated as dangerous goods. 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk

14.4. Packing group Not assigned.

14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

**IMDG** 

14.1. UN number Not regulated as dangerous goods. Not regulated as dangerous goods. 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

Not assigned.

Subsidiary risk

14.4. Packing group Not assigned.

14.5. Environmental hazards

Marine pollutant No.

**EmS** Not assigned. Not assigned. 14.6. Special precautions

for user

14.7. Maritime transport in bulk Not applicable.

according to IMO instruments

General information This product is not regulated as dangerous goods for solid. Shipped hot molten product requires a

class 9 "HOT" with statement: Elevated temperature material, liquid, N.O.S. 9, UN3257, III

(Polyolefinic blend).

# SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

#### **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

## Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

4700 - 4800 Series SDS EU 9/11

928749 Version #: 02 Revision date: 19-October-2022 Issue date: 16-August-2015

## Other EU regulations

#### Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Other regulations

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as **National regulations** 

amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

#### List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices References

ECHA: European Chemical Agency.

EPA: AQUIRE database

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

NLM: Hazardous Substances Data Base

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

None

Training information

Disclaimer

Follow training instructions when handling this material.

This material safety data sheet is offered for your information only. We believe the statements, technical information and recommendations contained here in are reliable, but are given without warranty or guarantee of any kind, expressed or implied. THE INTERNATIONAL GROUP, INC. assumes no responsibility for any loss, damage or expense, direct or consequential, arising from the use of our material. It is the responsibility of the user to determine the suitability and completeness of such information for the required use or application. We do not assume any legal responsibility for nor do we give permission, inducement or recommendation to practice any patented invention without a license. Further, it is the user's obligation to utilize this material in full compliance with all health, safety and environmental regulations.

4700 - 4800 Series SDS EU Revision date: 19-October-2022 Issue date: 16-August-2015 10 / 11

928749 Version #: 02

PRODUCT NUMBER	PRODUCT NUMBER	PRODUCT NUMBER
4706A	4819B	R-6049A
4706B	4820A	R-6059A
4708A	4820B	R-6084A
4709A	4822A	R-6136A
4713A	4824A	R-6171B
4719A	4825A	R-6171C
4721A	4825C	R-6171D
4723A 4727A	4825D 4826A	R-6209A R-6236A
4729A	4828A	R-6277A
4731A	4829A	R-6307B
4734A	4831A	R-6307C
4738A	4832A	R-6340C
4738B	4833A	R-6345A
4739A	4834A	R-6345B
4741A	4836A	R-6480A
4741S	4837A	R-6584A
4744A 4750A	4838A 4839A	R-6584B R-6584C
4752A	4841A	R-6584D
4753A	4842A	R-6584E
4754A	4843A	R-6611A
4756A	4844A	R-6613A
4757A	4848A	R-6629A
4757B	4848B	R-6723A
4758A	4848C	R-6723B
4760A	4848D	R-6828A
4760B 4761A	4848E 4849A	R-6828B R-6940A
4765A	4850A	R-6954A
4766A	4850B	R-6955C
4766B	4850C	R-6973A
4769A	4850E	R-6973B
4769B	4850G	R-6973C
4773A	4852A	R-6973D
4777A	4853A	
4783A	4858A	
4784A 4786A	4862A 4864A	
4786B	4867A	
4786D	4869A	
4786E	4870A	
4787A	4872A	
4789A	4874A	
4791A	4875A	
4793A	4876A	
4794A	4877A	
4796A 4797A	4877B 4878A	
4797B	4879A	
4798A	4880A	
4801A	4881A	
4802A	4882A	
4807A	4891A	
4809A	4892A	
4813A	4895A	
4816A	R-5825A	
4818A 4818B	R-5825B R-5847A	
4819A	R-5915A	
1010/1	1 10010/1	<u> </u>

4700 - 4800 Series SDS EU Revision date: 19-October-2022 Issue date: 16-August-2015