



THE INTERNATIONAL GROUP, INC.

SAFETY DATA SHEET

1. Identification

Product identifier	4700 - 4800 Series Products (Astorlite[®], Nochek[®], Parafflex[®], Synertive[®])
Other means of identification	
SDS number	4700 - 4800 Series (929125)_USA_English
Synonyms	See page 8
Recommended use	Further processing , Misc. multiple uses
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Company Name	The International Group Inc.
Address	50 Salome Dr. Toronto ON, M1S2A8, CA
Telephone	+1 416-293-4151
Emergency phone number	+1 416-293-4151 +1 800-561-3509
CHEMTREC (North America)	+1 800-424-9300

2. Hazard(s) identification

Physical hazards	Not classified.
Health hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	The mixture does not meet the criteria for classification.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Paraffinic Hydrocarbons	Proprietary	≤ 90
Fatty acid	Proprietary	< 17

Composition comments	The specific chemical identity and/or exact percentage of component(s) have been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.
-----------------------------	--

4. First-aid measures

Inhalation	Solid: No specific first aid measures noted. If fumes from heated product are inhaled: Move to fresh air. Call a POISON CENTER or doctor/physician if you feel unwell.
-------------------	--

Skin contact	Solid: No specific first aid measures noted. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water, and see a physician for removal of adhering material and treatment of burn.
Eye contact	Solid: No specific first aid measures noted. Exposure to fumes, vapors or smoke of over heated product can result in irritation of eyes. Direct contact of molten material will cause injury and burns. When handling of molten product eye shield must be worn at all times. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Should an accident occur, flush eyes with generous amounts of water for at least 15 minutes. Administer prompt first aid measures. Get medical attention if irritation develops and persists.
Ingestion	Solid: No specific first aid measures noted. Not acutely toxic by ingestion. If material is ingested, do not induce vomiting. Contact with hot product may cause severe burns. Get medical attention immediately.
Most important symptoms/effects, acute and delayed	Eye and skin contact: When heated, contact with molten product can cause injury and burns.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	By heating and fire, irritating vapors/gases may be formed. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Use water spray to cool unopened containers. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out.
General fire hazards	No unusual fire or explosion hazards noted.
6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Handle as a thermoplastic. With molten spills, allow the material to solidify and cool. Keep material out of sewers and watercourses by diking or impounding. Recover and place into appropriate containers for recycling or disposal, according to prevailing local, state and federal laws. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Allow material to solidify, and scrape up. Following product recovery, flush area with water. Small Spills: Where possible allow molten material to solidify naturally.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage

Precautions for safe handling

When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers. Do not handle until all safety precautions have been read and understood. Heat only in areas with appropriate exhaust ventilation. Do not breathe fume/mist/vapors. Avoid contact with molten material. When using, do not eat, drink or smoke. Observe good industrial hygiene practices. Do not empty into drains. Avoid release to the environment. Wash contaminated clothing before reuse. The material is a solid at room temperature exhibiting elevated temperature softening characteristics. Above its softening point, the material liquefies and flows more readily as the temperature increases. The material may be used as a hot liquid for application purposes and requires caution in handling.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Fatty acid	TWA	3 mg/m ³ 10 mg/m ³	Respirable fraction. Inhalable fraction.
Paraffinic Hydrocarbons	TWA	2 mg/m ³	Fume.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Paraffinic Hydrocarbons	TWA	2 mg/m ³	Fume.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear approved safety goggles. Wear a face shield when working with molten material.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other

The material may be utilized in molten form. Proper protective splash resistant clothing, thermal gloves, splash resistant shoes, and eye shields must be worn to prevent injury. Use molten material in well ventilated areas. When working in confined areas, use of appropriate respiratory gear is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Solid.

Form

Slabs, prills, pastilles or granules.

Color

White to dark amber.

Odor

None to strong petroleum odor.

Odor threshold

No data available.

pH

Not applicable.

Melting point/freezing point	114.8 - 257 °F (46 - 125 °C)
Initial boiling point and boiling range	> 572 °F (> 300 °C)
Flash point	> 392.0 °F (> 200.0 °C) ASTM D-92
Evaporation rate	< 0.01 (Butyl acetate = 1)
Flammability (solid, gas)	Will support a flame above flash point.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)	0.9 % v/v
Explosive limit - upper (%)	7 % v/v

Vapor pressure	< 0.01 mm Hg
Vapor pressure temp.	77 °F (25 °C)
Vapor density	> 5 (Air = 1)
Relative density	0.9 - 0.96 (H ₂ O=1)
Relative density temperature	77 °F (25 °C)

Solubility(ies)

Solubility (water)	< 0.1 %
Solubility temp. (water)	68 °F (20 °C)

Partition coefficient (n-octanol/water)	No data available.
--	--------------------

Auto-ignition temperature	No data available.
----------------------------------	--------------------

Decomposition temperature	No data available.
----------------------------------	--------------------

Viscosity	No data available.
------------------	--------------------

Other information

Partition coefficient (oil/water)	< 0.01
Percent volatile	< 1

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Decomposition of this product can generate carbon dioxide, carbon monoxide and other products such as aldehydes and ketones depending on conditions of oxidation.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Not relevant at normal room temperatures. When heated, irritating vapors may be formed. Wax fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons.
Skin contact	Health injuries are not known or expected under normal use. Molten material will produce thermal burns.
Eye contact	Health injuries are not known or expected under normal use. Molten material will produce thermal burns.
Ingestion	Health injuries are not known or expected under normal use. Contact with hot material can cause thermal burns which may result in permanent damage.

Symptoms related to the physical, chemical and toxicological characteristics	Eye and skin contact: Contact with molten material may cause thermal burns.
---	---

Information on toxicological effects

Acute toxicity	Not expected to be acutely toxic.
-----------------------	-----------------------------------

Components	Species	Test Results
Fatty acid (CAS Proprietary)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 hours
Skin corrosion/irritation	Not classified. Thermal burn hazard - contact with hot material may cause thermal burns.	
Serious eye damage/eye irritation	Not classified. Direct contact of molten product to the eyes will cause thermal burns and eye injury.	
Respiratory or skin sensitization		
Respiratory sensitization	Not classified.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	Not classified.	
Carcinogenicity	Not expected to be hazardous by OSHA criteria.	
IARC Monographs. Overall Evaluation of Carcinogenicity	Not listed.	
NTP Report on Carcinogens	Not listed.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	Not regulated.	
Reproductive toxicity	Not classified.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Solid product: Not likely, due to the form of the product.	
Chronic effects	Exposure to vapors, fumes, or smoke from molten material handled in confined areas can produce irritation of respiratory tracts, and possible physical discomfort to sensitive individuals.	
Further information	None.	
12. Ecological information		
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential	No data available on bioaccumulation.	
Mobility in soil	The product is insoluble in water.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	
13. Disposal considerations		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).	
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.	
14. Transport information		
DOT	Not regulated as dangerous goods.	
IATA	Not regulated as dangerous goods.	

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

General information This product is not regulated as dangerous goods for solid. Shipped hot molten product requires a class 9 "HOT" with statement: Elevated temperature material, liquid, N.O.S. 9, UN3257, III (Polyolefinic blend).

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Paraffinic Hydrocarbons (CAS Proprietary)

US. New Jersey Worker and Community Right-to-Know Act

Paraffinic Hydrocarbons (CAS Proprietary)

US. Pennsylvania Worker and Community Right-to-Know Law

Paraffinic Hydrocarbons (CAS Proprietary)

US. Rhode Island RTK

Paraffinic Hydrocarbons (CAS Proprietary)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	18-August-2015
Revision date	11-April-2018
Version #	02
HMIS® ratings	Health: 0 Flammability: 1 Physical hazard: 0

NFPA ratings



Disclaimer

This material safety data sheet is offered for your information only. We believe the statements, technical information and recommendations contained here in are reliable, but are given without warranty or guarantee of any kind, expressed or implied. THE INTERNATIONAL GROUP, INC. assumes no responsibility for any loss, damage or expense, direct or consequential, arising from the use of our material. It is the responsibility of the user to determine the suitability and completeness of such information for the required use or application. We do not assume any legal responsibility for nor do we give permission, inducement or recommendation to practice any patented invention without a license. Further, it is the user's obligation to utilize this material in full compliance with all health, safety and environmental regulations.

**PRODUCT
NUMBER**

4840A
4850B
4850C
4850E
4856A
4856C
4856E
4856F
4856G
4856H
4856M
4856N
4856P
4856Q
4856R
4856S
4856T
4856U
4857A
4857B
4857C
4857D
4857E
4857G
4857H
4857L
4857V
R-7113A
R-7127B