SAFETY DATA SHEET



1. Identification

Product identifier 6000 Series Products

Other means of identification

SDS number 6000 Series (929124)_Canada_English

Synonyms See page 9

Recommended use Further processing, Misc. multiple uses

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name The International Group Inc.

Address 50 Salome Dr.

Toronto

ON, M1S2A8, CA 416-293-4151

Telephone 416-293-4151 **Emergency telephone** 416-293-4151

2. Hazard identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statements

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

The components are not hazardous or are below required disclosure limits.

4. First-aid measures

Inhalation Solid: No specific first aid measures noted. If fumes from heated heated product are inhaled: Move

to fresh air. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact Solid: No specific first aid measures noted. If burned by contact with hot material, cool molten

material adhering to skin as quickly as possible with water, and see a physician for removal of

adhering material and treatment of burn.

Eye contact Solid: No specific first aid measures noted. Exposure to fumes, vapors or smoke of over heated

product can result in irritation of eyes. Direct contact of molten material will cause injury and burns. When handling of molten product eye shield must be worn at all times. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Should an accident occur, flush eyes with generous amounts of water for at least 15 minutes. Administer prompt first aid measures. Get

medical attention if irritation develops and persists.

Ingestion Solid: No specific first aid measures noted. Not acutely toxic by ingestion. If material is ingested,

do not induce vomiting. Contact with hot product may cause severe burns. Get medical attention

immediately.

6000 Series SDS Canada 929124 Version #: 02 Revision date: 14-May-2018 Issue date: 18-August-2015 1 / 9

Most important symptoms/effects, acute and delayed

Eye and skin contact: When heated, contact with molten product can cause injury and burns.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

General information

If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

By heating and fire, irritating vapours/gases may be formed. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Cool containers exposed to heat with water spray and remove container, if no risk is involved. In the event of fire and/or explosion do not breathe fumes. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up Keep unnecessary personnel away. Do not breathe mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.

Handle as a thermoplastic. With molten spills, allow the material to solidify and cool. Keep material out of sewers and watercourses by diking or impounding. Recover and place into appropriate containers for recycling or disposal, according to prevailing local, state and federal laws.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Allow material to solidify, and scrape up. Following product recovery, flush area with water

Small Spills: Where possible allow molten material to solidify naturally. Scrape up.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage

Precautions for safe handling

When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers. Do not handle until all safety precautions have been read and understood. Heat only in areas with appropriate exhaust ventilation. Do not breathe fume/mist/vapors. Avoid contact with molten material. When using, do not eat, drink or smoke. Observe good industrial hygiene practices. Do not empty into drains. Avoid release to the environment. Wash contaminated clothing before reuse. The material is a solid at room temperature exhibiting elevated temperature softening characteristics. Above its softening point, the material liquefies and flows more readily as the temperature increases. The material may be used as a hot liquid for application purposes and requires caution in handling.

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS). When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers.

6000 Series SDS Canada 929124 Version #: 02 Revision date: 14-May-2018 Issue date: 18-August-2015 2/9

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Value Components	s Type	Value	Form
Fatty acid	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Hydrocarbons	TWA	5 mg/m3	Inhalable fraction.
Paraffinic hydrocarbons	TWA	2 mg/m3	Fume.
Components	Туре	Value	Form
Mineral oil	TWA	5 mg/m3	Inhalable fraction.
Canada. Alberta OELs (Occupatio Components	nal Health & Safety Code, Scl Type	nedule 1, Table 2) Value	Form
Fatty acid	TWA	10 mg/m3	
Hydrocarbons	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Paraffinic hydrocarbons	TWA	2 mg/m3	Fume.
Components	Туре	Value	Form
Mineral oil	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Canada. British Columbia OELs. (Safety Regulation 296/97, as ame		s for Chemical Substances, C	Occupational Health and
Components	Туре	Value	Form
Fatty acid	TWA	10 mg/m3	
Organic oil	TWA	3 mg/m3	Respirable mist.
		10 mg/m3	Mist.
Paraffinic hydrocarbons	TWA	2 mg/m3	Fume.
Components	Туре	Value	Form
Mineral oil	TWA	1 mg/m3	Mist.
Canada. Manitoba OELs (Reg. 217	//2006, The Workplace Safety	And Health Act)	
Components	Туре	Value	Form
Fatty acid	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Hydrocarbons	TWA	5 mg/m3	Inhalable fraction.
Paraffinic hydrocarbons	TWA	2 mg/m3	Fume.
Components	Туре	Value	Form
Mineral oil	TWA	5 mg/m3	Inhalable fraction.
Canada. Ontario OELs. (Control o Components	f Exposure to Biological or Cl Type	nemical Agents) Value	Form
Fatty acid	TWA	10 mg/m3	
Paraffinic hydrocarbons	TWA	2 mg/m3	Fume.
Components	Туре	Value	Form
Mineral oil	TWA	5 mg/m3	Inhalable fraction.
Canada. Quebec OELs. (Ministry o	of Labor - Regulation respecti Type	ng occupational health and s Value	afety) Form
Hydrocarbons	STEL	10 mg/m3	Mist.

 6000 Series
 SDS Canada

 929124
 Version #: 02
 Revision date: 14-May-2018
 Issue date: 18-August-2015
 3 / 9

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components **Form Type** Value Organic oil **STEL** 10 mg/m3 Mist. **TWA** 10 mg/m3 Mist. Paraffinic hydrocarbons **TWA** 2 mg/m3 Fume. Components **Type** Value **Form** Mineral oil **STEL** 10 mg/m3 Mist. **TWA** 5 mg/m3 Mist.

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Eye wash facilities and emergency

shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved safety goggles. Wear a face shield when working with molten material.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other The material may be utilized in molten form. Proper protective splash resistant clothing, thermal

gloves, splash resistant shoes, and eye shields must be worn to prevent injury. Use molten material in well ventilated areas. When working in confined areas, use of appropriate respiratory

gear is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Slabs, prills, pastilles or granules.

Colour White to light gray or tan.

Odour None.

Odour threshold No data available.
pH Not applicable.

Melting point/freezing point 30 - 70 °C (86 - 158 °F) Initial boiling point and boiling > 300 °C (> 572 °F)

range

Flash point > 150.0 °C (> 302.0 °F) ASTM D-93

Evaporation rate < 0.01 (Butyl acetate = 1)

Flammability (solid, gas) No data available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) No data available.

Explosive limit - upper No data available.

(%)

Vapour pressure < 0.01 mm Hg
Vapour pressure temp. 25 °C (77 °F)
Vapour density > 5 (Air = 1)
Relative density temperature 25 °C (77 °F)

6000 Series SDS Canada 929124 Version #: 02 Revision date: 14-May-2018 Issue date: 18-August-2015 4 / 9

Solubility(ies)

Solubility (water) < 0.1 % 20 °C (68 °F) Solubility temp. (water)

Partition coefficient (n-octanol/water)

No data available.

Auto-ignition temperature No data available. **Decomposition temperature** No data available. No data available. Viscosity

Other information

Explosive properties Not explosive. Not oxidising. Oxidising properties

Partition coefficient

(oil/water)

< 0.01

Percent volatile Negligible

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use. Hazardous polymerisation does not

occur.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the Conditions to avoid

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

Decomposition of this product can generate carbon dioxide, carbon monoxide and other products

such as aldehyldes and ketones depending on conditions of oxidation.

11. Toxicological information

Information on likely routes of exposure

Not relevant at normal room temperatures. When heated, irritating vapours may be formed. Wax Inhalation

fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons.

Skin contact Health injuries are not known or expected under normal use. Molten material will produce thermal

burns.

Health injuries are not known or expected under normal use. Molten material will produce thermal Eye contact

Health injuries are not known or expected under normal use. Contact with hot material can cause Ingestion

thermal burns which may result in permanent damage.

Symptoms related to the physical, chemical and toxicological characteristics Eye and skin contact: Contact with molten material may cause thermal burns.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Test Results Components **Species**

Mineral oil (CAS Proprietary)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

Aerosol

LC50 Rat > 5 mg/l

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation

Not classified. Thermal burn hazard - contact with hot material may cause thermal burns. Not classified. Direct contact of molten product to the eyes will cause thermal burns and eye injury. Serious eye damage/eye

irritation

6000 Series SDS Canada 929124 Version #: 02 Revision date: 14-May-2018 Issue date: 18-August-2015 5/9 Respiratory or skin sensitisation

Respiratory sensitisation Not classified.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicity Not classified.

Not classifiable as to carcinogenicity to humans. Carcinogenicity

ACGIH Carcinogens

Mineral oil (CAS Proprietary) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Mineral oil (CAS Proprietary) Not classifiable as a human carcinogen.

Reproductive toxicity Specific target organ toxicity - Not classified. Not classified.

single exposure

Not classified. Specific target organ toxicity -

repeated exposure

Solid product: Not likely, due to the form of the product. **Aspiration hazard**

Exposure to vapors, fumes, or smoke from molten material handled in confined areas can Chronic effects

produce irritation of respiratory tracts, and possible physical discomfort to sensitive individuals.

Further information None.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results**

Mineral oil (CAS Proprietary)

Aquatic Acute

Crustacea **LL50** Invertebrates (Invertebrates) 100 mg/l Fish **LL50** 10 mg/l Fish

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential No data available on bioaccumulation. Mobility in soil

The product is insoluble in water.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

6000 Series SDS Canada 929124 Version #: 02 Revision date: 14-May-2018 Issue date: 18-August-2015 6/9 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Inventory neme

General information

This product is not regulated as dangerous goods for solid. Shipped hot molten product requires a class 9 "HOT" with statement: Elevated temperature material, liquid, N.O.S. 9, UN3257, III (WAX).

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

On inventory (vector)*

Yes

Yes

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

0-----

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AIIC)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Taiwan Chemical Substance Inventory (TCSI)

Toxic Substances Control Act (TSCA) Inventory

16. Other information

Taiwan

Issue date 18-August-2015
Revision date 14-May-2018

Version No. 02

United States & Puerto Rico

6000 Series SDS Canada 929124 Version #: 02 Revision date: 14-May-2018 Issue date: 18-August-2015 7 / 9

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

This material safety data sheet is offered for your information only. We believe the statements, technical information and recommendations contained here in are reliable, but are given without warranty or guarantee of any kind, expressed or implied. THE INTERNATIONAL GROUP, INC. assumes no responsibility for any loss, damage or expense, direct or consequential, arising from the use of our material. It is the responsibility of the user to determine the suitability and completeness of such information for the required use or application. We do not assume any legal responsibility for nor do we give permission, inducement or recommendation to practice any patented invention without a license. Further, it is the user's obligation to utilize this material in full compliance with all health, safety and environmental regulations.

 6000 Series
 SDS Canada

 929124
 Version #: 02
 Revision date: 14-May-2018
 Issue date: 18-August-2015
 8 / 9

PRODUCT	PRODUCT
NUMBER	NUMBER
6006A 6017A 6017B 6019A 6023A 6024A 6025A 6025B 6027A 6028A 6030A 6031C 6031D 6031E 6031G 6035A 6036A 6036B 6036C 6037A 6038A 6041A 6045A 6045A 6045A 6045A 6045A 6045A 6055A 6060B 6061A 6060B 6061A 6062A 6060B 6061A 6062A 6063A 6095A 6098A 6098A 6098B 6301A 6302A 6304A 6305A 6306A 6307A 6308A 6307A 6308A 6307A 6308A 6307A 6308A 6307A 6308A 6307A 6308A 6307A 6308A 6307A 6308A 6307A 6308A 6309A R-2322A R-2778A R-2779A R-3619A R-3641B R-4863A R-5930B R-5930B R-5930B R-5930A R-5930A R-5930B R-5930A R-6043A	R-6043B R-6043C R-6078A R-6078B R-6105A R-6115A R-6129B R-6129B R-6211A R-6324A R-6354B R-6354C R-6354B R-6540D R-6540D R-6540D R-6570A R-6589A R-6540D R-6771A R-6771B R-6771A R-6771B R-6773A R-6872A R-6913F R-6996A R-7017A R-7017A R-7041A

6000 Series SDS Canada 929124 Version #: 02 Revision date: 14-May-2018 Issue date: 18-August-2015 9 / 9