

USA: 1007 East Spring Street · Titusville, PA 16354 · Toll Free: 1-800-852-6537 · Telephone: (814) 827-4900 · Fax: (814) 827-2363 Canada: 50 Salome Drive · Toronto, Ontario M1S 2A8 · Toll Free: 1-800-561-3509 · Telephone: (416) 293-4151 · Fax: (416) 293-5858 Website: www.igiwax.com

PETROFIBE® 0201A

PETROFIBE® **0201A** is a dark brown industrial grade petrolatum of medium-hard consistency.

PETROFIBE® 0201A finds economical use in applications not requiring the more expensive USP or NF grades.

PHYSICAL PROPERTIES

	ASTM	SPECIFICATIONS		
TEST METHODS	METHOD	Minimum	Maximum	TYPICAL
Drop Melt Point °F (°C)	D 127	130 (54.4)	160 (71.1)	145 (62.8)
Kinematic Viscosity, cSt @ 212°F (100°C)	D 445	13.0	23.0	18.0
ASTM Color	D 6045			6.3
Cone Penetration, dmm @ 77°F (25°C)	D 937	140	180	160

Note: Physical properties for which ONLY a typical value is listed are included as additional information but may not be printed on the COA.

TYPICAL USES:

Rubber plasticizer / Leather finishes / Rust preventative / Soldering paste / Printing inks / Industrial putty

FDA STATUS:

This product is not intended for food contact.

3/4/13

WARRANTY DISCLAIMER STATEMENT