USA: 1007 East Spring Street · Titusville, PA 16354 · Toll Free: 1-800-852-6537 · Telephone: (814) 827-4900 · Fax: (814) 827-2363 Canada: 50 Salome Drive · Toronto, Ontario M1S 2A8 · Toll Free: 1-800-561-3509 · Telephone: (416) 293-4151 · Fax: (416) 293-5858 Website: www.igiwax.com

PARAFFLEX® 4750A

PARAFFLEX[®] **4750A** is a high quality and versatile blended wax developed for the manufacture of molded taper and pillar candles. PARAFFLEX[®] 4750A is fully formulated and requires no additives other than color and fragrance. Candles made with PARAFFLEX[®] 4750A are opaque and can hold fragrance up to 6% (by weight).

PHYSICAL PROPERTIES

	ASTM	SPECIFICATIONS		
TEST METHODS	METHOD	Minimum	Maximum	TYPICAL
Congealing Point °F (°C)	D 938	142 (61.1)	149 (65)	146 (63.3)
Kinematic Viscosity, cSt @ 212°F (100°C)	D 445	4.5	6.0	5.3
Saybolt Color	D 6045	+28		
Needle Penetration, dmm @ 77°F (25°C)	D 1321	10	16	12
Needle Penetration, dmm @ 110°F (43.3°C)	D 1321	40	55	45

Note: Physical properties for which ONLY a typical value is listed are included as additional information but may not be printed on the COA.

FDA STATUS:

Please contact an IGI representative for information concerning the FDA status of this product.

10/15/20

WARRANTY DISCLAIMER STATEMENT